

# L901 Industrial Color Label Printer


## Powerful in Both Roll-to-Roll and Inline Applications

The L901 combines industrial design, exceptional image quality, and high production speeds with a new ability to service and maintain the printhead “on-the-fly.” This makes the L901 perfect for long roll-to-roll jobs or inline integration with label finishers, applicators, dispensers and more.


Producing vibrant full-color prints in high resolution of 1600dpi is now more economical than ever, thanks to five high-capacity 250ml CMYKK ink cartridges delivering a new ultra-low cost per label.

### Key Features

- ✓ Low ink cost per label
- ✓ Variable data capability
- ✓ Professional print quality
- ✓ Designed for inline operation



Presses / Finishers



Roll to Roll



Print & Apply

### Water-Resistant Labels

The L901 Plus model has Watershield™ for increased moisture resistance.

This optional technology is perfect for labels that may be exposed to moisture, such as chilled beverages, foods, chemicals, or pharmaceutical products.



Powered by 



### Mid-job printhead maintenance

Revolutionary print engine allows for mid-job cleaning. Crucial for full inline operation

### Touchscreen Operation

Easily store files, run and pause jobs, or perform maintenance tasks through a user-friendly interface



### Industrial build quality

Designed for all-day printing—either roll-to-roll or inline—in a production environment

### Professional image quality & resolution

Exceptionally crisp text, barcodes, and images with vibrant color and rich blacks



# L901 Specifications

## Printer:

<b>Print method:</b>	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
<b>Inks:</b>	Dye-based, 250mL CMYKK (1.25L total)
<b>Print resolution:</b>	1600 x 1600 dpi – 1600 x 800 dpi
<b>Print speed:</b>	6 inches (152 mm) per second – 12 inches (305 mm) per second
<b>Print width:</b>	8.5 inches (216 mm)
<b>Cutter/sheeter:</b>	Powered

## Media:

<b>Media Size:</b>	Width: 2"–9" (50.8 mm–229 mm) Length: 2"–48" (50.8 mm–1220 mm)	<b>Media sensors:</b>	Gap (movable), continuous, black mark
<b>Thickness:</b>	Minimum 0.005" (0.13 mm) Maximum 0.01" (0.3 mm, including liner)	<b>Die-cut gap:</b>	Minimum 0.125" (3.0 mm) Maximum 0.3" (8.0 mm)
<b>Core diameter*:</b>	Requires 3" (76.2 mm) cardboard core	<b>Black mark:</b>	3 mm wide, 25.4 mm long on left
<b>Unwind/Rewind*:</b>	10" (250mm) outside diameter	<b>Substrates:</b>	Compatible with a wide range of paper, polyester, polypropylene, and vinyl label stocks

\*with optional XL Unwind/Rewind system, shown below

## General:

<b>Interfaces:</b>	USB 2.0, TCP/IP (Manual IP configuration or DHCP), GPIO available for external device control
<b>Operating system:</b>	Windows 7, 8, and 10 (32 and 64 bit)
<b>Barcode font:</b>	1D Barcode at least Grade B (Code39) with 10mils bar width
<b>2D code printing:</b>	2D Barcode at least Grade B (PDF417) with 10mils cell size
<b>Operating temperature:</b>	15°–35° C (59°–95°F) at RH 20–80%
<b>Overall dimensions**:</b>	22.5" (572 mm) W, 20.5" (521 mm) D, 14" (356 mm) H
<b>Weight:</b>	85 lb (38.5 kg)
<b>Rated voltage:</b>	AC 110V – 220V, auto-sensing
<b>Warranty:</b>	One year

### Optional XL Unwind/Rewind System

For high-capacity roll-to-roll production.  
Visit our website or contact us for details.



\*\*Dimensions with XL Unwind/Rewind System:  
59.5" (1512 mm) W, 20.5" (521 mm) D, 23" (585 mm) H



**In-House Label Solutions for Every Level of Production**

[afinialabel.com](http://afinialabel.com)

**US Office**  
sales@afinialabel.com  
+1 888.215.3966



**UK Office**  
sales@afinia.co.uk  
+44 (0) 845.250.7949



**AFINIA LABEL®**